


Barrier Film

Metallised, Broad Seal, High Hot Tack & Barrier

HST-1 (HSB) MO T095

Structure



Description

It is a co-extruded, one side metallised and other side low heat sealable & high hot tack Bi-axially Oriented Polypropylene film.

Features

- Excellent performance in VFFS & HFFS machine
- Good metal adhesion to film
- Very good barrier to moisture and light
- Very good gas barrier
- High heat seal strength
- High hot tack strength
- Broad seal range

Applications

- As a laminate for snack food, bakery & confectionery packaging application

Typical Values

Properties	Ref.	Units	ASTM # / Test Method	HST-1 (HSB) MO T095
Physical Data				
Average Thickness		micron	D-374-C	18
		gauge		72
		mils		0.7
Thickness Variation		% (±)		3
Density		g/cc		0.905
Average Substance		g/m ²		16.3
Kinetic COF	UT-UT		D-1894	0.35 - 0.45
Yield		m ² /kg	D-4321	61.3
		in ² /lb		43098
Optical Data				
Optical Density			CTM	2.2
Mechanical Data				
Tensile Strength	MD	kg/ cm ²	D-882	1300 -1500
	TD			2600 -2800
Elongation	MD	%	D-882	150 -190
	TD			40 -70
Thermal Data				
Shrinkage (120°C/248°F, 5 min.)	MD	%	D-1204	3.0 - 5.0
	TD			1.0 - 3.0
Heat Seal Range		°C / °F	CTM	95 - 145 / 203 - 293
Heat Seal Strength		g/25mm	CTM	>500
Hot Tack Strength		g/30mm	115°C	395
Barrier Data				
MVTR (38°C, 90%RH)		g/m ² /day	F-1249	< 0.25
MVTR (100°F, 90%RH)		g/100in ² /day		< 0.01
OTR (23 °C, 0%RH)		cc/m ² /day	D-3985	< 30
OTR (74 °F, 0%RH)		cc/100in ² /day		< 1.93

CTM : Cosmo Test Method MD : Machine Direction TD : Transverse Direction LTS: low temperature sealing UT = Un-treated
 Disclaimer : The information provided above is based on COSMO FILMS LTD's conclusive tests, which are indicative only and provided as guidelines. They do not constitute a guarantee of any specific product attributes or the suitability of products for specific applications.

Cosmo Films Limited

1008,DLF Tower -A, Jasola District Centre, New Delhi - 110 025, India, T: + 91-11-49 49 49 49,
 E-mail: sales.enquiry@cosmofilms.com | www.cosmofilms.com